

EVERYTHING COVERED



P-SERIES P1000/240/423

TECHNICAL DETAILS

FRAME SPECIFICATIONS

Span width:	10.00m
Eave height:	2.40m
Ridge height (internal):	4.23m
Roof pitch:	20°
Main profile (upright / truss):	89/48/3mm (2-channel) or 110/48/3mm (4-channel)
Eave connection type:	Galvanised steel insert
Longest component::	5.37
Aluminium type:	Hard pressed / high impact extruded anodised aluminium to DIN 4112
Steel connections:	European-hot dipped galvanised to DIN 50976
Wind Loading:	80km/hr (0.30kN/m2)

ACCESSORIES

Steel sub-framed flooring system
Cassette flooring system
High peaked roof conversions
Hexagonal end bays
Octagonal end bays
Lean-to extensions
Linings
Double door units
Single door units
Entrance porches
Ramp units
Portal beams
Adjustable leg inserts
Gutter systems
Stake pullers

ROOF OPTIONS

Clear PVC
Translucent PVC
OPAQUE PVC
High peaked roof conversions

WALLING OPTIONS

Translucent PVC walling
OPAQUE PVC walling
PVC window walls
ABS Solid cassette walling system
Glass cassette walling system

P-SERIES P1000/240/423
Created on 25 July 2017



P-SERIES P1000/240/423

3D DRAWING



CAD DRAWING

